# Vericert OOPSLA 2021 Artifact

This artifact should support the claims made in the paper "Formal Verification of High-Level Synthesis". In the paper, our tool Vericert was referred to as using the temporary name "HLSCert". The claims that can be verified by the paper are the following:

- The mechanised proof of correctness of the translation from C into Verilog is provided and can be checked and rerun.
- All 27 PolyBench benchmarks can be recompiled using Vericert.
- The cycle counts of Vericert on the benchmarks can be checked and compared against LegUp 4.0.
- If Vivado is downloaded separately, then the whole performance section can be checked, including all the graphs that appear in the paper.

#### Claims that are not supported by the artifact

Unfortunately, we could not include our version of LegUp 4.0 in the artifact due to license restrictions. In addition to that, LegUp was recently bought by Microchip and renamed to SmartHLS<sup>1</sup>, which means that it also cannot be freely downloaded anymore either, and the original open source version of LegUp 4.0 is not available anymore due to server issues in Toronto<sup>2</sup>. We have tried contacting the authors of LegUp in Toronto, but have not heard back yet on if our version of LegUp can be shared in the artifact.

Instead, we have included the net lists that LegUp generated from the benchmarks in the artifact, with all the optimisation levels that were tried, however, it does mean that these cannot be verified again and that other optimisation options cannot be tried.

In addition to that, the Vivado synthesis tool by Xilinx<sup>3</sup> is also commercial (but free to download), and therefore cannot be bundled into the artifact either. This synthesis tool was used to get accurate timing information about how the design would run on an FPGA, and also give the area that the design would take up on the FPGA. To be able to reproduce these results, it would therefore need Vivado to be set up so that the scripts can run.

<sup>&</sup>lt;sup>1</sup>https://www.microsemi.com/product-directory/fpga-design-tools/5590-hls# software-download

<sup>&</sup>lt;sup>2</sup>https://legup.eecg.utoronto.ca

<sup>&</sup>lt;sup>3</sup>https://www.xilinx.com/support/download.html

# Kick the tyres

First, the docker image needs to be downloaded and run, which contains the git repository:

docker pull ymherklotz/vericert
docker run -it ymherklotz/vericert sh

Then, one just has to go into the directory which contains the git repository and open a nix-shell, which will load a shell with all the correct dependencies loaded:

cd /vericert nix-shell

Then, any commands can be run in this shell to run vericert, which has already been compiled and can be found in the /vericert/bin directory. For a quick test that it is working, a few very simple examples in the /vericert/test directory can be run by using the following inside of the /vericert directory:

#### make test

If this finishes without errors, it means that Vericert is working correctly.

# **Detailed Artifact Description**

This section describes the detailed instructions to get the results for the different sections of the paper, first describing the structure of the proof and how to execute Vericert manually, to finally running Vericert on the benchmarks and get the cycle counts for the Vericert designs as well as the precompiled LegUp designs.

#### Directory structure of Vericert

The main directory structure of Vericert is the following:

- /src Contains all the Coq and OCaml source files used for Vericert. The whole proof of correctness is therefore in this directory.
- /lib This directory contains CompCert, on which Vericert is built upon. Vericert tries to separate CompCert and uses it only as a library, redefining a different top-level.
- /benchmarks Contains the PolyBench/C benchmarks used as an evaluation in the paper, which are stored under polybench-syn for the benchmarks without dividers, and polybench-syn-div for the benchmarks with dividers.
- /docs Contains a website and an org-mode file with some light documentation of the tool.

- /example Contains some interesting observations that were made during the development, which are not directly relevant to Vericert.
- /include Contains the divider implementation which can be imported and used in C files to get the better performance out of Vericert, instead of using native division.
- /ip Contains hardware divider implementations which will be used in the future instead of the software implementation that is currently used in /include.
- /scripts Contains some miscellaneous scripts and the Dockerfile which has been added for this artifcat.

## Description of the proof

The proof is mostly located in /src/hls, which contains the proof of correctness of the 3AC to HTL transformation, as well as the transformation from HTL to Verilog. Any other files in the /src/hls directory that are not mentioned below are there for future optimisations such as scheduling, which are not used.

- /src/Compiler.v The very top-level of the proof is located here and it contains the main proof of the compiler, which is the proof that the transf\_hls function is correct, which takes C and outputs Verilog. The main proof of correctness is in the Theorem called transf\_c\_program\_correct, which says that if the transf\_hls function succeeded, that the backward simulation should hold between C and Verilog.
- /src/common This directory contains some common library extensions and proofs that are used in other parts of Vericert. This includes the proof of correctness of Section 2.2.3, which is located in /src/common/IntegerExtra.v under the Theorem shrx\_shrx\_alt\_equiv.
- /src/hls/Verilog.v This file contains the whole Verilog semantics, together with the proof that the Verilog semantics are deterministic. This implements Section 3 from the paper.
- src/hls/Veriloggen.v This file contains the generation of Verilog from HTL.
- src/hls/Veriloggenproof.v This file contains the correctness proof of the generation
  of Verilog from HTL.
- /src/hls/HTL.v This file contains the definition of the HTL intermediate language, together with its semantics.
- /src/hls/HTLgen.v This file contains the generation of HTL from 3AC, which is the first step in the HLS transformation.

- /src/hls/HTLgenspec.v This file contains the high-level specification of the translation from 3AC into HTL, together with a proof of correctness of the specification.
- /src/hls/HTLgenproof.v This file contains the proof of correctness of the HTL generation from 3AC, where the main parts of the proof are the generation of Verilog operations, as well as the change in the memory model (load and store instructions).
- /src/hls/Memorygen.v This file contains the definition and proof of the transformation which replaces naïve loads and stores into a proper RAM, which is described in Section 2.2.2.
- /src/hls/ValueInt.v Contains our definition of values that are used in the Verilog semantics, and differ from the values used by CompCert, as they don't have a pointer type anymore.
- /src/hls/Array.v Contains our definition of the memory model, which is a dependently typed array, which encodes its length. This is much more concrete than CompCert's abstract memory model, and closer to how it is actually modelled in hardware.
- /src/hls/AssocMap.v Definition of association maps, which is the type that is used for  $\Gamma$  and  $\Delta$  in Section 3.

# How to manually compile using Vericert

To compile arbitrary C files, the following command can be used:

vericert main.c -o main.v

Which will generate a Verilog file with a corresponding test bench. The Verilog file can then be simulated by using the Icarus Verilog simulator:

iverilog main.v -o main ./main

This should print out the return value from the main function in addition to the number of cycles that it took to execute the hardware design.

#### Getting cycle counts for Vericert

There are two benchmark sets for which the results are given in the paper:

- /vericert/benchmarks/polybench-syn Contains the PolyBench/C benchmark without any dividers, and instead the dividers are replaced by calls to sdivider and smodulo in /vericert/include/hls.h.
- /vericert/benchmarks/polybench-syn-div Contains the PolyBench/C benchmark with dividers.

To get the cycle counts for Vericert from the benchmarks, the benchmarks can be compiled using the following:

cd /vericert/benchmarks/polybench-syn

or

#### cd /vericert/benchmarks/polybench-syn-div

depending on which benchmark should be run, and then running:

make

This will generate all the binaries for the simulation and execution of the C code. The cycle counts of the hardware can then be gotten by running:

#### ./run-vericert.sh

This can take a while to complete, as simulation of hardware is quite slow. After around 30 minutes, there should be a exec.csv file which contains the cycle counts for each of the 27 benchmarks.

# Getting the cycle counts for LegUp

Unfortunately, the benchmarks cannot be compiled from C to Verilog using LegUp, as it could not be included in the artifact, and does not seem to be freely available anymore.

However, our compiled Verilog designs from LegUp have been included for all the optimisation options that were tested for in the paper in Section 5.

To get the cycle counts, it suffices to go into an arbitrary directory, and run the following script, where the command line arguments select which set of cycle counts to generate:

```
/vericert/scripts/run-legup.sh [syn|syn-div] \
        [opt|no_opt|no_chain|no_opt_no_chain]
```

For example, to run the LegUp benchmarks with no LLVM optimisations and no operation chaining, on the PolyBench/C benchmark with no dividers, one can run the following command:

#### /vericert/scripts/run-legup.sh syn no\_opt\_no\_chain

This will take some 30 minutes to run as well, and will generate an exec\_legup.csv file, with the name of the benchmark and it's cycle count.

#### Comparing the results

To compare the results to the results presented in the paper, the main comparison that is supported by this artifact is to compare the cycle counts to the ones used to generate the graphs in the evaluation section of the paper.

The /data/data directory contains all the raw data which was used to generate the graphs in Section 5. This data can therefore be used to examine the cycle counts used to draw the graphs. This raw data can be examined better in /data/data/results.org, which includes the tables in a nicer format.

The legup-\* csv files contain the raw size, timing and cycle count for the various LegUp configurations on the different benchmarks. vericert-\* is the equivalent but for Vericert. Then, to draw the graphs, the actual csv files that are used are:

rel-size-\* This contains the relative size of each run (denoted by slice in the csv files) compared to fully optimised LegUp. This is obtained by taking the slice value of the tool being considered (LegUp with some optimisation turned off, or Vericert), and dividing that by the number of slices present in fully optimised LegUp.

# $\frac{\text{slice}_t}{\text{slice}_{\text{legup\_opt}}}$

rel-time-\* This performs the same computation as for the size comparison, comparing
to LegUp with all optimisations turned on, but instead compares the following
values: cycles × delay:

 $\frac{\operatorname{cycles}_t \times \operatorname{delay}_t}{\operatorname{cycles}_{\operatorname{legup\_opt}} \times \operatorname{delay}_{\operatorname{legup\_opt}}}$ 

Where t is the tool being considered.

## Compiling the graph

A tex file is included in the /data/data directory, which unfortunately can only be compiled outside of the docker file, but will recreate the graphs from the paper using the csv files in the directory. This can be achieved using the following commands:

```
docker create ymherklotz/vericert:v1.0 # returns container ID
docker cp $container_id:/data/data .
docker rm $container_id
cd data
pdflatex graphs
```

#### Running with Vivado

Finally, for the adventurous that downloaded Vivado, there are some short instructions for running it on single examples. Running synthesis on a benchmark will normally take around 20 minutes to an hour depending on the benchmark, so it might take a long time to complete.

First, create a new directory and copy the synthesis script into it, as well as the Verilog file that should be synthesisd. For example, once make was run in the benchmarks folder, one of the benchmarks can be selected for Vericert, such as jacobi-1d:

```
mkdir synthesis
cd synthesis
cp /vericert/scripts/synth.tcl .
cp /vericert/benchmarks/polybench-syn/stencils/jacobi-1d.v main.v
```

Then Vivado can be run in batch mode in that directory to generate the report:

vivado -mode batch -source synth.tcl

Once this completes, the important results of the synthesis should be available in encode\_report.xml, where each field will also be present in the relevant CSV file, which is this case is /data/data/vericert-nodiv.csv.

#### Rebuilding the Docker image

The docker image can be completely rebuilt from scratch as well, by using the Dockerfile that is located in the Vericert repository at /vericert/scripts/docker/Dockerfile, which also contains this document.

To rebuild the docker image, one first needs to download the LegUp results for the benchmarks without divider<sup>4</sup> and with divider<sup>5</sup>, as well as the csv folder with all the raw results<sup>6</sup>. The tar files should be placed into the same directory as the Dockerfile. Then, in the docker directory, the following will build the docker image, which might take around 20 minutes:

docker build .

Then, using the hash it can be run in the same way as the docker container that was linked to this artifact:

docker run -it <hash> sh

<sup>&</sup>lt;sup>4</sup>https://imperialcollegelondon.box.com/s/ril1utuk2n88fhoq3375oxiqcgw42b8a
<sup>5</sup>https://imperialcollegelondon.box.com/s/94clcbjowla3987opf3icjz087ozoi10

<sup>&</sup>lt;sup>6</sup>https://imperialcollegelondon.box.com/s/nqoaquk7j5mj70db16s6bdbhg44zjn52